IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

N/A = Not Applicable

1. Name/Description of battery

TJEP Li-Ion Battery 6,0 Ah (TJEP #103964)

1a. Name/Description of the cells inside the battery

INR18650-30Q Samsung SDI

The test summary of the cells inside the battery must either be presented or under checkpoint 9 and 9a it must be confirmed that the UN 38.3 test summary for the cells is available.

2. Manufacturer of battery		
Name	Aimsak Inc.	
Address		
Phone	+82-70-5032-7409	
Email	chrisoh@aimsak.com	
Website	www.aimsak.com	

2a. Manufacturer of the equipment (if the battery is contained in equipment)		
Name	Aimsak Inc.	
Address	171, Yangcheongsongdae-gil, Ochang-eup, Cheongwon-gu Cheongsju-si, Chungcheongbuj-do, Korea	
Phone	+82-70-5032-7409	
Email	chrisoh@aimsak.com	
Website	www.aimsak.com	

3. Test laboratory of battery			
Name	KCTL Inc.		
Address	52-20 Sinjeong-ro 41 beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do, Korea		
Phone	+82-31-326-6700		
Email			
Website	www.kctl.co.kr/en/		

4. ID-number and date			
Unique test report identification number	KR19-YBM0017	Date of test report	2019.06.28 - 2019.12.16



IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)

TJEP Li-Ion Battery 6,0 Ah

DESCRIPTION OF BATTERY

5. Mark the type of battery with an "●"				
Lithium ion battery	Lithium metal ba	ttery O		
Lithium hybrid battery				
6. Parameters				
Mass in gram (g):		729		
Lithium ion: Indicate watt-hour rating (Wh):		127,44		
Lithium metal: Indicate lithium metal content in gram (g):				
Lithium hybrid: Indicate lithium metal content in gram (g) and watt-hour rating (Wh):				
Element rigoria. Indicate utiliani metat content in grani (g) and wate nour rating (vvii).				
7. Physical description of battery				
24V Rechargeable Lithium-Ion Slide on Battery				
8. Model numbers				
103964 TJEP Li-Ion Battery 6,0 Ah f/TJEP RC20A/RC30A Rod cutter				

TESTS AND RESULTS

9. List of tests conducted and results - Mark N/A, pass or fail with an "•"	N/A	pass	fail
T1 - Altitude simulation		•	
T2 - Thermal Test		•	
T3 - Vibration		•	
T4 - Shock		•	
T5 - External Short Circuit		•	
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm See check point 1a and 9a.	•	0	0
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells having a diameter of less than 18 mm. See check point 1a and 9a.	•	0	0
T7 - Overcharge		•	
T8 - Forced Discharge, only valid for cells. See check point 1a and 9a.	•		



IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)

TJEP Li-Ion Battery 6,0 Ah

9a.UN 38.3 Test Confirmation for the Cells inside the battery When no separate document for the cells is provided, this confirms that the cells inside the battery (see checkpoint 1.a.) have successfully passed the UN 38.3 test. In this case under checkpoint 9 the T.6 and T.8 must be marked as "passed" and here under 9.a. "Cell UN 38.3 Test confirmed" needs to be ticked.		ell N 38.3 T Infirmed	est	UN 38.3	Cell Test NOT irmed	0
10. Reference to assembled battery testing requirements			1			
					N/A	
11. Reference to the revised edition of the Manual of Tests and Criteria used and	d to ar	nendme	nts th	ereto		
ADDITIONAL SUPPLIER INQUIRY						
12. Quality management system for manufacturing batteries Does the manufacturer of the battery manufacture the products based on a documented quality management system according to transport regulations?				YES	NO	\bigcirc
13. Are the following parameters exceeded? Lithium ion battery: more than 100 Wh Lithium metal battery: more than 2 g Lithium Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh			•	YES	NO	
Check point 14 – 16 need to be answered when 13 has been ticked "YES":						
14. Does each battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?			(YES	NO	
15. Is each battery equipped with an effective means of preventing external short of	circuits	;?	(YES	NO	Ŏ
16. Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)?		N/A	<u> </u>	YES	NO	O
17. Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion batteri	ies and		polyr			
State of Charge (SoC) max. 30 %		N/A		YES	NO	

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)

TJEP Li-Ion Battery 6,0 Ah

BATTERIES INSTALLED IN EQUIPMENT

18. Check point 18 needs to be answered when the batteries are installed in articles:				
18.a) Only button cells enclosed?				
18.b) Number of enclosed batteries per equipment				
When the equipment is inl	tentionally active/switched on during transport e	.g. data loggers:		
18.c) Confirmation that no dangerous amount of heat is emitted from the equipment N/A YES NO				
18.d) Confirmation that the equipment when transported by air fulfills the defined air transport standards for electromagnetic radiation according to DO-160 N/A YES NO				
19. Place, Date	20. Title, Surname, First name	21. Company stamp and signature		
Sunds, 20.01.2020	Operations Director, Ebbe Kærgaard Hornstrup	Ebbe KYDEERE KYOCERALINA SE GALANING ASS		